Gen4D: Synthesizing Humans and Scenes in the Wild

Jerrin Bright, Zhibo Wang, Yuhao Chen, Sirisha Rambhatla,
David Clausi, John Zelek
University of Waterloo, Waterloo, Ontario, Canada

CVPR Nashville JUNE 11-15, 2025

TL;DR

We introduce **Gen4D**, an automated pipeline for synthesizing diverse, realistic 4D human animations, and use it to build **SportPAL**, a large-scale synthetic sports dataset for human-centric vision tasks.

Motivation

Collecting diverse, high-quality human motion data in real-world sports is costly and logistically difficult. While **synthetic datasets** offer a promising alternative, most rely on **fixed 3D assets, and repetitive animations**, resulting in limited diversity across appearance, motion, and viewpoint; ultimately restricting generalization to in-the-wild settings.

Problem Statement

Can we fully automate the synthesis of lifelike human animation from raw motion to scene synthesis without any manual 3D modeling?

Key Contributions

- **Gen4D**: A fully automated pipeline for synthesizing lifelike human avatars with realistic animations.
- **SportPAL**: A large-scale, richly annotated synthetic dataset spanning baseball, ice hockey, and soccer, designed for human-centric vision tasks.

Prompt Modeling

- Uses text templates to guide avatar generation via diffusion models.
- Captures diversity in appearance attributes like ethnicity, body type, age, hair, and clothing.
- Attributes are combined programmatically to avoid repetition and ensure balanced sampling.
- Enables generation of highly varied and realistic human avatars without manual asset design.



The proposed Method: Gen4D

1. **Motion Extraction:** obtain motion representation from internet videos.
2. **Canonical Human Gaussians:** generates diverse human avatars via text-guided diffusion and Gaussian splatting in canonical space.
3. **Scene Composition:** Animate avatars with motion, render from multiple viewpoints, and synthesize human-aware backgrounds using diffusion-based scene generation.



Qualitative Results

(a) (b) (c)

(a) Examples of 3D canonical avatar representations; **(b)** Final rasterized synthetic frames with avatar animation and pose-aware backgrounds; **(c)** Qualitative visualizations of pose estimation results trained on SportPAL using TokenPose [1].

SportPAL

- Includes 580K+ synthetic frames across baseball, ice hockey, and soccer.
- Rich annotations: 2D/3D poses, SMPLX parameters, bounding boxes, and action labels.
- Built from 50 unique subjects with varied ethnicity, body types, clothing, and viewpoints.

SportPAL dataset split

Sport	Split	#Subjects	#Clips	#Frames
Baseball	Train	15	1,000	253,869
	Valid	15	304	80,810
	Test	5	300	71,875
Icehockey	Train	10	195	75,468
	Valid	10	50	18,867
	Test	5	12	7,487
Soccer	Train	10	116	57110
	Valid	10	30	14,277
	Test	5	5	3639
Total	-	**50**	**2,012**	**583,403**

Quantitative Results

Impact of fine-tuning with cross-domain sports

Sport	Method	AP^5↑	AP^{10}↑	AP^{15}↑
Icehockey	w/o finetuning	62.75	96.92	99.91
	w/ finetuning	**63.47** (+0.72)	**98.10** (+1.18)	**99.98** (+0.07)
Soccer	w/o finetuning	67.28	92.56	98.51
	w/ finetuning	**71.46** (+4.18)	**94.68** (+2.12)	**99.13** (+0.62)

Acknowledgement

Vision and Image Processing Research Group
VIP lab
vip.uwaterloo.ca
NSERC CRSNG
Mitacs
Orioles
https://jerrinbright.github.io/projects/gen4D.html

References

[1] Yanjie Li, Shoukui Zhang, Zhicheng Wang, and et al. Tokenpose: Learning keypoint tokens for human pose estimation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 11313–11322, 2021.